



SHUTTERMAX® *eco*

MAXimum Security, Insulation and Smart Operation

The European designed **SHUTTERMAX® eco** is perfect for external applications where security and equipment integration is needed. The insulating properties of the individual slats provide temperature control to reduce energy consumption and when coupled with our smart controller provides seamless integration to a broad range of docking equipment.

AUSTRALIAN MADE
EUROPEAN DESIGNED
GERMAN DRIVE TECHNOLOGY




Insulated Slat – front view



Compact side guide design



Insulated Slat – back view



GFA Safedrive®



Technical Datasheet – <i>SHUTTERMAX® eco</i>		
Application	External/Internal	
Dimension	Max width	5000mm
	Max height	4500mm
Opening Speed	0.2m/sec	
Closing Speed	0.2m/sec	
Door Curtain	Anodised Aluminium external profile bonded to a hardened PVC longitudinal profile filled with polyurethane foam	Standard
	Electrostatic Paint	Optional
	Double Glazed Window Profiles	Optional
Door Frame	Galvanised Steel	Standard
	Powdercoated	Optional
Top Roll Tube	Galvanised Steel	Standard
Guide System	Hardened PVC profile end guides and guide rails	Standard
	GfA Safedrive® with integrated safety brake & manual hauling chain	Standard
Safety	Safedrive® integrated safety brake	Standard
	Door-line Safety PE Beam	Standard
	Door Head Lintel and Bottom Profile Seal	Standard
	Manual Chain Over-ride	Standard
Thermal Insulation	U = 0.875 / R = 1.14	23mm Profile
Acoustic Insulation	30 dB	
Wind Load Rating	Gusts > 120km/hr (Class 3)	Standard (size dependant)



MAX Door Solutions Pty. Ltd.

P: 1300 793 378

sales@maxdoors.com.au

56 Export Drive, Molendinar, QLD, 4214

PO Box 777, Biggera Waters QLD, 4216

www.maxdoors.com.au